

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 070 603 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

24.01.2001 Bulletin 2001/04

(51) Int. Cl.⁷: B60B 27/00

(21) Application number: 00114983.0

(22) Date of filing: 20.07.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 22.07.1999 US 359236

(71) Applicant:

Meritor Heavy Vehicle Systems, LLC
Troy, MI 48084 (US)

(72) Inventor: Riley, Andrew John

Plas Goulbourne, Wrexham LL 13 9LX (GB)


(74) Representative:

Kitzhofer, Thomas, Dipl.-Ing.
Patentanwälte Prinz & Partner GbR
Manzingerweg 7
81241 München (DE)

(54) Retaining assembly for an axle hub and bearing assembly

(57) An axle assembly (20) for supporting wheels is provided that has a spindle (24) defining an axis of rotation with a threaded end portion (34). A hub assembly (26) is supported by the spindle and is adapted to support the wheels. A bearing assembly (32) is arranged adjacent to the threaded end portion and is interposed between the spindle and the hub assembly for permitting low friction rotation of the hub assembly relative to

the spindle about the axis. An end nut (38) is secured to the threaded end portion of the spindle for retaining the bearing assembly and the hub assembly on the spindle. A washer is interposed between said bearing assembly and the end nut wherein the washer (62) secures the end nut to the spindle for preventing rotation of the end nut about the axis.



EP 1 070 603 A2

Description

BACKGROUND OF THE INVENTION

[0001] This invention relates to an axle assembly for supporting wheels and, more specifically, to a retaining assembly used to retain a hub assembly and bearing assembly onto a spindle of the axle assembly.

[0002] Axle assemblies support wheels on their distal ends, or spindles. Hub assemblies, which carry the wheels, are supported on the spindles by bearing assemblies. Typically, end nuts are fastened to the spindles to secure the bearing and hub assemblies to the spindle. An additional retaining device is usually employed to ensure that the end nut does not come unfastened from the spindle. For example, a split pin may be installed in a hole transverse to the spindle axis and adjacent to the end nut. However, if the hole and pin are not precisely placed relative to the location of the installed end nut, the pin will be difficult to install or will allow the nut to loosen until it contacts the pin. Therefore, what is needed is a retaining device that prevents the end nut from loosening from its originally installed location.

SUMMARY OF THE INVENTION AND ADVANTAGES

[0003] The present invention provides an axle assembly for supporting wheels that has a spindle defining an axis of rotation with a threaded end portion. A hub assembly is supported by the spindle and is adapted to support the wheels. A bearing assembly is arranged adjacent to the threaded end portion and is interposed between the spindle and the hub assembly for permitting low friction rotation of the hub assembly relative to the spindle about the axis. An end nut is secured to the threaded end portion of the spindle for retaining the bearing assembly and the hub assembly on the spindle. A washer is interposed between said bearing assembly and the end nut wherein the washer secures the end nut to the spindle for preventing rotation of the end nut about the axis.

[0004] Accordingly, the above provides an improved mechanism for retaining the hub assembly and bearing assembly on the spindle of an axle assembly.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Other advantages of the present invention can be understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

Figure 1 is an end view of the axle assembly of the present invention partially broken away to show the drum brakes;

Figure 2 is a cross-sectional view of the axle taken along line 2 - 2 in Figure 1;

Figure 3 is an enlarged view of the bearing area shown in Figure 2;

Figure 4 is a top elevational view of the retaining clip;

Figure 5 is a perspective end view of the axle assembly of the present invention;

Figure 6 is a top elevational view of the washer assembly;

Figure 7 is a cross-sectional view of the washer assembly taken along line 7 - 7 in Figure 6;

Figure 8 is a top elevational view of the staking washer of the washer assembly;

Figure 9 is a cross-sectional view of the staking washer taken along line 9 - 9 in Figure 8;

Figure 10 is a top elevational view of the retaining nut of the present invention; and

Figure 11 is a side elevational view of the retaining nut in Figure 10.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0006] Referring to Figures 1 and 2, an axle assembly 20 has an axle housing 22 with a spindle 24 at each of its distal ends. The spindle 24 defines an axis of rotation, A, about which a hub assembly 26 rotates. The hub assembly 26 is supported by the spindle 24 and is adapted to support the wheels 28. The hub assembly 26 also supports a brake drum 30, or a rotor for disc brakes (not shown). A bearing assembly 32 is arranged between the spindle 24 and hub assembly 26 to permit low friction rotation of the hub assembly 26 about the axis A. The spindle 24 has a threaded end portion 34 adjacent to the bearing assembly 32 with an end nut 38 fastened to the threaded end portion 34 for retaining the bearing assembly 32 and hub assembly 26 on the spindle 24. A hub cap 39 is secured to the hub assembly 26 to seal the bearing assembly 32 from the outside environment.

[0007] Referring now to Figure 3, a washer assembly 42 is arranged between the bearing assembly 32 and the end nut 38. The washer assembly 42 secures the end nut 38 to the spindle 24 for preventing rotation of the end nut 38 about the axis A, which is described in more detail below. The bearing assembly 32, or bearing cartridge, has a two piece cone 44 press fit onto the spindle 24 and a cup 46 press fit into an interior surface 47 of the hub assembly 26. Roller bearings 48 are arranged radially between the cone 44 and cup 46 and are located relative to one another by a cage 50. Seals 52 are arranged between the cone 44 and cup 46 at the outer ends of the bearing assembly 32 to prevent debris from penetrating the bearing assembly 32.

[0008] The hub assembly 32 has a groove 54 on the interior surface 47 adjacent to the cup 46. A C-shaped retaining clip 56, best shown in Figure 4, is seated in the groove 54 to retain the bearing assembly 32 in the hub assembly 26 and prevent movement of the bearing

assembly 32 along the axis A. The retaining clip 56, which has a circular cross-section, is larger than the groove 54 so that the retaining clip 56 must be compressed to insert the clip 56 into the groove 54.

[0009] Referring now to Figure 5 in conjunction with Figure 3, the end nut 38 is prevented from loosening by rotating about the axis A. To this end, the washer assembly 42 is secured to the spindle 24 and the end nut 38. The washer assembly 42 includes a locating washer 62 and a staking washer 64 that are secured to one another. The locating washer 62 engages a groove 60 in the spindle 24 that is generally parallel with the axis A, and the staking washer 64 is deformed into engagement with the end nut 38.

[0010] Referring to Figures 6-9, the locating washer 62 has a first inner diameter 65 with a tab 66 that extends radially inwardly from the first inner diameter 65 and engages the groove 60 thereby preventing the washer assembly 42 from rotating about the spindle 24. The staking washer 64 includes a second inner diameter 69 with at least one prong 70 extending transversely from the second inner diameter 69. The locating washer 62 has at least one notch 68 that receives a corresponding prong 70 for securing the locating 62 and staking 64 washers together. The prongs 70 may be bent outward from the inner diameter 69 to ensure that the washers 62, 64 are secured together. The staking washer 64 has an outer diameter 72 with an arcuate flange 74 extending transversely from the outer diameter 72, best shown in Figures 8 and 9.

[0011] Referring to Figures 10 and 11, the end nut 38 has an outer perimeter 76 adjacent to the arcuate flange 74. The end nut 38 has at least one recess 80. A portion 78 of the flange 74 is deformed into engagement with the recess 80 of the end nut 38, preferably so that the portion 78 shears and the portion 78 abuts the recess 80 to ensure that the end nut 38 cannot rotate relative to the washer assembly 42. Preferably, the end nut 38 has three recesses 80 disposed radially about the end nut 38 with the flange 74 deformed into engagement with only one recess 80. By only deforming one portion 78 of the flange 74, the same washer assembly 42 to be used two more times. It can be seen that the retaining assembly of the present invention prevents the end nut 38 from rotating relative to the spindle 24 and loosening from its originally installed location.


[0012] The invention has been described in an illustrative manner, and it is to be understood that the terminology that has been used is intended to be in the nature of words of description rather than of limitation. Obviously, many modifications and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims the invention may be practiced otherwise than as specifically described.


Claims


1. An axle assembly for supporting wheels comprising:
 - a spindle defining an axis of rotation and having a threaded end portion;
 - a hub assembly supported by said spindle and adapted to support the wheels;
 - a bearing assembly adjacent to said threaded end portion and interposed between said spindle and said hub assembly for permitting low friction rotation of said hub assembly relative to said spindle about said axis;
 - an end nut secured to said threaded end portion of said spindle for retaining said bearing assembly and said hub assembly on said spindle; and
 - a washer interposed between said bearing assembly and said end nut wherein said washer secures said end nut to said spindle for preventing rotation of said end nut about said axis.
2. The assembly as set forth in claim 1 wherein said washer comprises a washer assembly including a locating washer and a staking washer secured to one another, wherein said locating washer engages said spindle and said staking washer engages said end nut for preventing rotation of said washer assembly and said end nut about said axis.
3. The assembly as set forth in claim 2 wherein said spindle includes a groove generally parallel with said axis, and said locating washer includes a first inner diameter with a tab extending radially inwardly therefrom which engages said groove.
4. The assembly as set forth in claim 3 wherein said first inner diameter of said locating washer includes at least one notch, and said staking washer includes a second inner diameter with at least one prong extending transversely therefrom for engaging said at least one notch and securing said locating and staking washers together.
5. The assembly as set forth in claim 4 wherein end nut includes an outer perimeter, and wherein said staking washer includes an outer diameter with an arcuate flange extending transversely therefrom adjacent to said outer perimeter, a portion of said flange engaging said end nut.
6. The assembly as set forth in claim 5 wherein said end nut has at least one recess, said flange deformed into engagement with said at least one recess.

7. The assembly as set forth in claim 6 wherein said at least one recess comprises three recess, said flange deformed into engagement with one of said three recesses.
8. A method for retaining a hub assembly and bearing assembly on a spindle of an axle assembly comprising the steps of:
- (a) installing a hub assembly and bearing assembly onto a spindle having an axis;
 - (b) installing a washer onto the spindle adjacent to the bearing assembly, wherein the washer is rotationally fixed to the spindle relative to the axis;
 - (c) fastening an end nut onto spindle adjacent to the washer; and
 - (d) deforming the washer into engagement with the end nut for rotationally fixing the end nut relative to the spindle.
9. The method as set forth in claim 8 wherein said washer comprises a washer assembly including a locating washer and a staking washer secured to one another, wherein said locating washer engages said spindle and said staking washer engages said end nut for preventing rotation of said washer assembly and said end nut about said axis.
10. The method as set forth in claim 9 wherein said spindle includes a groove generally parallel with said axis, and said locating washer includes a first inner diameter with a tab extending radially inwardly therefrom which engages said groove.
11. The method as set forth in claim 10 wherein said first inner diameter of said locating washer includes at least one notch, and said staking washer includes a second inner diameter with at least one prong extending transversely therefrom for engaging said at least one notch and securing said locating and staking washers together.
12. The method as set forth in claim 11 wherein end nut includes an outer perimeter, and wherein said staking washer includes an outer diameter with an arcuate flange extending transversely therefrom adjacent to said outer perimeter, a portion of said flange engaging said end nut.
13. The method as set forth in claim 12 wherein said end nut has at least one recess, said flange deformed into engagement with said at least one recess.
14. The method as set forth in claim 13 wherein said portion of said flange is sheared when said flange is deformed into engagement with said at least one
- recess.
15. The method as set forth in claim 14 wherein said at least one recess comprises three recess, said flange deformed into engagement with one of said three recesses.

FIG. 1











FIG. 5






FIG. 9





FIG. 8



SECTION "X-X"





FIG. 10




FIG. 11

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 070 603 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
06.08.2003 Bulletin 2003/32

(51) Int Cl.7: **B60B 27/00, F16B 39/10**

(43) Date of publication A2:
24.01.2001 Bulletin 2001/04

(21) Application number: 00114983.0

(22) Date of filing: 20.07.2000

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Riley, Andrew John**
Plas Goulbourne, Wrexham LL 13 9LX (GB)

(74) Representative: **Kitzhofer, Thomas, Dipl.-Ing.**
Patentanwälte Prinz & Partner GbR
Manzingerweg 7
81241 München (DE)


(30) Priority: 22.07.1999 US 359236

(71) Applicant: **Meritor Heavy Vehicle Systems, LLC**
Troy, MI 48084 (US)

(54) Retaining assembly for an axle hub and bearing assembly

(57) An axle assembly (20) for supporting wheels is provided that has a spindle (24) defining an axis of rotation with a threaded end portion (34). A hub assembly (26) is supported by the spindle and is adapted to support the wheels. A bearing assembly (32) is arranged adjacent to the threaded end portion and is interposed between the spindle and the hub assembly for permit-

ting low friction rotation of the hub assembly relative to the spindle about the axis. An end nut (38) is secured to the threaded end portion of the spindle for retaining the bearing assembly and the hub assembly on the spindle. A washer is interposed between said bearing assembly and the end nut wherein the washer (62) secures the end nut to the spindle for preventing rotation of the end nut about the axis.

**FIG. 3****EP 1 070 603 A3**

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 11 4983

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCl.7)
X	US 5 618 143 A (CRONIN II PHILIP J ET AL) 8 April 1997 (1997-04-08)	1	B60B27/00 F16B39/10
Y	* column 2, line 45 - column 3, line 11 * * abstract; figures 1-3 *	2,3,8	
X	WO 97 18925 A (WARN IND INC) 29 May 1997 (1997-05-29)	1	
Y	* page 10, line 3 - line 37 * * abstract; figures 10,11 *	2,3,8	
Y	DE 32 32 150 A (MUELLENBERG RALPH) 1 March 1984 (1984-03-01) * page 9, line 30 - page 10, line 17 * * abstract; figures 1-4 *	8	
Y	US 2 561 224 A (FRIEDRICH PISCHEK ET AL) 17 July 1951 (1951-07-17)	2,3	
A	* column 2, line 47 - line 50 * * column 1-4 *	4,9	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	US 4 737 058 A (JONSSON LARS R ET AL) 12 April 1988 (1988-04-12) * column 2, line 12 - line 42 * * abstract; figures 1-4 *	1,8	B60B F16B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 5 June 2003	Examiner Verkerk, E
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

EPO FORM 1503 (03/02) (P4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 11 4983

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-06-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5618143	A	08-04-1997	AU	4144396 A	31-05-1996
			WO	9614515 A1	17-05-1996
			US	5772373 A	30-06-1998
WO 9718925	A	29-05-1997	US	5772373 A	30-06-1998
			AU	4992396 A	11-06-1997
			EP	0865344 A1	23-09-1998
			JP	2000500556 T	18-01-2000
			WO	9718925 A1	29-05-1997
DE 3232150	A	01-03-1984	DE	3232150 A1	01-03-1984
			HU	36902 A2	28-10-1985
			IT	1170207 B	03-06-1987
US 2561224	A	17-07-1951	NONE		
US 4737058	A	12-04-1988	SE	445762 B	14-07-1986
			DE	3124041 A1	25-03-1982
			FR	2485657 A1	31-12-1981
			GB	2078896 A , B	13-01-1982
			IT	1171320 B	10-06-1987
			JP	1648934 C	13-03-1992
			JP	3009324 B	08-02-1991
			JP	57033213 A	23-02-1982
			SE	8004660 A	25-12-1981

EPO FORM P0489

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.